

GSW226

Superb Winter Properties • Safety & Stability



Steer



Overview

Rim Sizes:22.5

Aspect Ratio:55-80mm

Section Width:295-385

Speed Rating:K-M

Features	Benefits
Pattern design with many deep sipes	Provides excellent steering and braking performances in the most severe winter conditions
Rib pattern design with an optimized footprint	Provides highest level of sideforces for best steering properties in winter conditions
Optimized tread pattern layout	Improves driver comfort
Wide shoulder ribs	Optimum stability and driver comfort
Achieves 3PMSF performance requirement	Meets legal requirements for 3PMSF certified winter tyres

Giti - GSW226 offers 5 different tyre sizes

	Tire Size	PR	Load Index	Speed Rating	Approved Rim	Outer Diameter (mm)	Tread Depth (mm)	Max Load(kg)	kPa	PSI
TUBELESS	295/80R22.5	18PR	154/149	M	9.00	1044	16.5	3750/3250	850/850	123/123
	315/80R22.5	18PR	158/150(154/150)	L(M)	9.00	1076	16.8	4250/3350	900/900	131/131
	315/70R22.5	18PR	156/150(154/150)	L(M)	9.00	1014	15.5	4000/3350	900/900	131/131
	385/65R22.5	20PR	164(160)	K(L)	11.75	1072	16	5000	900	131
	385/55R22.5	18PR	158(160)	L(J)	12.25	996	15.5	4250	850	123